

1. Consumabili

Contenitori/Capsule e navicelle

1 Vetri da orologio, vetro comune

Bordo molato. Conforme ai requisiti DIN 12341. Classe idrolitica 3.

Ø mm	Pz./Cf.	Codice
40	1	9.263 004
50	1	9.263 005
60	1	9.263 006
70	1	9.263 007
80	1	9.263 008
90	1	9.263 009
100	1	9.263 010
110	1	9.263 011
120	1	9.263 013
125	1	9.263 012
150	1	9.263 015
200	1	9.263 020
250	1	9.263 025



2 Vetri da orologio, Vetro Borosilicato 3.3

Bordo ribruciato. Conforme ai requisiti DIN 12341. Autoclavabile.

Ø mm	Pz./Cf.	Codice
50	10	9.263 470
60	10	9.263 471
70	10	9.263 472
80	10	9.263 473
100	10	9.263 474
125	10	9.263 475
150	10	9.263 476
200	10	9.263 477



3 Vetri da orologio, DURAN®

Bordo ribruciato. Conforme ai requisiti DIN 12341. Autoclavabili.

DURAN Group

Ø mm	Pz./Cf.	Codice
40	1	9.263 424
50	1	9.263 432
60	1	9.263 434
80	1	9.263 441
100	1	9.263 446
125	1	9.263 452
150	1	9.263 457
200	1	9.263 461
250	1	9.263 466



4 Vetri da orologio, PP

Con base. Sterilizzabili a 121°C.

Kartell

Ø mm	Pz./Cf.	Codice
60	1	9.263 526
80	1	9.263 528
100	1	9.263 530
125	1	9.263 532



5 Capsule per evaporazione, DURAN®

Forma sferica, fondo piatto, con becco. Conforme ai requisiti DIN12336, autoclavabile.

DURAN Group

Capacità ml	Ø bordo mm	Altezza mm	Pz./Cf.	Codice
15	50	25	1	9.000 032
45	60	30	1	9.000 034
60	70	35	1	9.000 038
90	80	45	1	9.000 041
170	95	55	1	9.000 044
320	115	65	1	9.000 049
600	140	80	1	9.000 054
1500	190	100	1	9.000 059
2500	230	130	1	9.000 063

